

TEMP. (°C) / ALTITUDE(M)	0 °C	10 °C	20 °C	30 °C	40 °C	50 °C
0	1.00	1.00	1.00	1.00	1.00	0.99
100	1.00	1.00	1.00	0.99	0.98	0.97
200	1.00	1.00	1.00	0.99	0.98	0.97
300	1.00	1.00	1.00	0.99	0.98	0.97
400	1.00	1.00	1.00	0.99	0.98	0.97
500	1.00	1.00	1.00	0.99	0.98	0.97
600	1.00	1.00	0.99	0.98	0.97	0.96
700	1.00	1.00	0.99	0.98	0.97	0.96
800	1.00	1.00	0.99	0.98	0.97	0.96
900	1.00	1.00	0.99	0.98	0.97	0.96
1,000	1.00	0.99	0.98	0.97	0.96	0.95
1,100	1.00	0.99	0.98	0.97	0.96	0.95
1,200	1.00	0.99	0.98	0.97	0.96	0.95
1,300	1.00	0.99	0.98	0.97	0.96	0.95
1,400	1.00	0.98	0.98	0.97	0.96	0.95
1,500	1.00	0.98	0.97	0.96	0.95	0.94
1,600	1.00	0.98	0.97	0.96	0.95	0.94
1,700	0.99	0.98	0.97	0.96	0.95	0.94
1,800	0.99	0.98	0.97	0.96	0.95	0.93
1,900	0.98	0.97	0.96	0.95	0.94	0.92
2,000	0.98	0.97	0.96	0.95	0.94	0.91
2,100	0.98	0.97	0.96	0.95	0.92	0.89
2,200	0.98	0.97	0.96	0.94	0.91	0.88
2,300	0.97	0.96	0.95	0.93	0.90	0.87
2,400	0.97	0.96	0.95	0.92	0.89	0.86
2,500	0.97	0.96	0.94	0.91	0.88	0.85
2,600	0.97	0.96	0.93	0.90	0.87	0.84
2,700	0.96	0.95	0.92	0.89	0.85	0.83
2,800	0.96	0.94	0.91	0.88	0.84	0.81
2,900	0.95	0.92	0.89	0.86	0.83	0.80
3,000	0.94	0.91	0.88	0.85	0.82	0.79

※ REMARK : TURBOCHARGED ENGINES

R410OZD, R4105ZD, R4105IZLD, R6105AZLD, R6105IZLD, R6113AZLD, R6126ZLD4, R6126ZLD5