



GENERATOR SET

Standby	kVA	850
	kW	680
Prime	kVA	775
	kW	620
Engine Speed	r.p.m	1500
Voltage	V	230/401
Power Factor	Cos Phi	0,8

CERTIFICATES

◆ CE Certificate

- ◆ 2006/42/EC Machinery Safety Directive
- ◆ 2014/30/EU Electromagnetic Compatibility Directive
- ◆ 2014/35/EU Low Voltage Directive
- ◆ 2000/14/EC By Equipment Used in the Open Field
- ◆ Regulation on Noise Emission in the Created Environment
- ◆ EN 12100:2010, TS EN 60201-1, EN 55011, EN 61000-6-4, EN 61000-4-11, EN 61000-4-8, EN 610000-4-5, EN 610000-4-2, EN 610000-4-2, EN 12601, TS ISO 8528-1-12

◆ TSE Certificate of Conformity to Turkish Standards

- ◆ TS EN 60034-1:2010
- ◆ TS ISO 8528-5
- ◆ TS ISO 8528-4
- ◆ TSE Service Place Qualification Certificate

◆ ISO 9001:2015 Quality Management System Certificate

- ◆ ISO 14001:2015 Environmental Management System Certificate
- ◆ OHSAS 18001:2007 Occupational Health and Safety Management
- ◆ ISO 10002:2014 Customer Satisfaction Management. System Cer.
- ◆ TS ISO/IEC 25051:2015 Software Engineering Certificate
- ◆ Republic of Turkey Ministry of Trade, After Sales Services
- ◆ 1500 hl Salt Water Test Certificate TS EN ISO/IEC 17025
- ◆ Domestic Goods Certificate
- ◆ Manufacturing Competence Certificate
- ◆ Industrial Registry Certificate
- ◆ Capacity Report
- ◆ Trademark Registration Certificate
- ◆ UKR-Sepro
- ◆ Mitsubishi OEM Manufacturer Certificate





ENGINE

Brand		Mitsubishi
Model		S12A2-PTA
Tip		4 stroke - diesel
Aspiration		Turbo Charged
Cooling System		WaterCooled
Cylinder Quantity	pcs	12
Bore x Stroke	mm	150x160
Relocation	lt	33,93
Compression Ratio		14.5:1
Main Power/Speed	kW/r.min	775
Standby Power/Speed	kW/r.min	850
Fuel Consumption 50	lt	84,2
Fuel Consumption 75	lt	124,6
Fuel Consumption 100%	lt	166,6
Oil Fuel Ratio	%	≤0.2%
Start Mode		Elektronik
Fuel Injection System		pump-line-nozzle (2x in-line pump)
Dimensions (LxWxH)	(mm)	2060x1382x1542
Dry Weight (kg)		3400



ALTERNATOR


Brand		Maranello
Model		M900
Output Voltage	V	230/400
Frequency	HZ	50
Automatic Voltage Regulation	±%	0,5
Alternator Standby Power	kVA	900
Alternator Continuous Use Power	kVA	800
Power Factor	Cosφ	0,8
Number of Cables		6
Winding Pitch		2/3
Protection Class		IP23/H
Warning System		Kendinden İkazlı
AVR Model		MX341B
Performance - PF 0.8 / 75% Load	%	94

DIMENSIONS



WITHOUT CABIN

Length (L) x Width (W) x Height (H)	mm	3950x2100x2570
Weight	kg	N/A
Fuel Tank Capacity	lt	1490



WITH CANOPY

Length (L) x Width (W) x Height (H)	mm	5450x2100x3330
Weight	kg	N/A
Fuel Tank Capacity	lt	1490

SOUND ISOLATION CABINET FEATURES

- ◆ Container and modular cabin production
- ◆ 65-75db. sound insulation
- ◆ Anti-vibration system
- ◆ Grilles for cooling and air circulation
- ◆ Special attachments for easy transportation
- ◆ Insulated transparent cover for easy access to the control cabinet
- ◆ Hidden exhaust
- ◆ Emergency stop button

CONTROL PANEL



D500 MK3



- ◆ 4-band GPRS modem (optional)
- ◆ USB Device
- ◆ RS-232 (2400-57600baud)
- ◆ J1939-CANBUS
- ◆ Geolocation with GSM
- ◆ GPS support (RS-232)

- ◆ Internet Centric Monitoring
- ◆ Send SMS messages (optional)
- ◆ Emailing (optional) Free PC software
- ◆ re: Rainbow Plu
- ◆ Modbus RTU

ATS PANEL

Güçbir Generator offers robust, versatile and compact solutions to transfer basic loads and electrical distribution systems from one power source to another with ATS panels. Güçbir's contactors, motorized switches and changeoverbased ATSs range from 40A to 6300 A and can be supplied externally for various applications. Also available internally switchgear inside the ATS panels, which can be supplied by ABB, SIEMENS, SCHNEIDER, GE, LS, HYUNDAI, TELERGON, SOCOMEC and ANDELI are internationally recognized trademarks.



OPTIONAL FEATURES

- ◆ Medium voltage alternator,
- ◆ Remote radiator applications
- ◆ Automatic refueling system
- ◆ Fuel tank, oil pan, instrument panel, alternator, coil heaters,
- ◆ Alternator with dual AVR and PMG
- ◆ Synchronization systems, Generator output switch,
- ◆ Mains-Generator transfer switches,
- ◆ Cabins in volumes suitable for special insulation demands
- ◆ Seismic solutions
- ◆ Trailer
- ◆ Remote monitoring
- ◆ SMPS 12/24V 10A

CONTROL PANEL

- ◆ Deepsea Control Devices
- ◆ Emko Control Devices
- ◆ ComAp Control Devices
- ◆ DEIF Control Devices

